

## PERKINS RANGE OF SOUND-PROOF GENERATOR SETS SP30/B - SP108/B



### SOUNDPROOF GENSET CHARACTERISTICS

#### HIGHLY CORROSION RESISTANT CONSTRUCTION

- Body made from special treated steel sheet.
- Stainless steel or cast aluminium locks and hinges.
- Zing plated or stainless steel fasteners.
- 2.5mm thick Sheet treated by grit blast Sa 2½.
- Two pack of epoxy paint system.

#### EXCELLENT ACCESS FOR MAINTENANCE

- Full length extra wide doors on each side.
- Doors top hung and supported by gas struts.
- Top hinged doors provide a shelter when open.
- Lube oil and cooling water drains piped to exterior of the canopy.

#### SECURITY AND SAFETY

- Control panel viewing window to easily view status of generating set.
- Emergency stop button mounted externally.
- Cooling fan and battery charging alternator fully guarded.
- Exhaust silencing system totally enclosed for operator safety.

### DIMENSIONS AND WEIGHTS

Sound-proof Genset Cont. Model	Rating Power 400V/50HZ		Length: mm	Width: mm	Height: mm	Net Weight: kg
	kW	kVA				
SP30/B	30	38	2340	970	1740	1250
SP34/B	34	42	2340	970	1740	1260
SP36/B	36	45	2550	1000	2810	1300
SP40/B	40	50	2550	1000	2810	1400
SP48/B	48	60	2550	1000	2810	1460
SP56/B	56	70	2550	1000	2810	2120
SP68/B	68	85	3120	1130	2910	2140
SP72/B	72	90	3120	1130	2910	2120
SP80/B	80	100	3120	1130	2910	2120
SP91/B	91	114	3120	1130	2910	2140
SP108/B	108	135	3120	1130	2910	2200